



**CONFORMS WITH REGULATIONS**

|              |                      |
|--------------|----------------------|
| <b>NMFC:</b> | Item 296 – Liquid 2A |
| <b>UN:</b>   | N/A                  |

**NOMINAL DIMENSIONS**

|                              |         |
|------------------------------|---------|
| <b>Inside Diameter:</b>      | 15-1/2" |
| <b>Inside Height:</b>        | 20-1/4" |
| <b>Outside Height:</b>       | 21-1/4" |
| <b>Tare Weight (approx):</b> | 9.6#    |
| <b>Net Packing Weight:</b>   | 400#    |

**NOMINAL CAPACITY**

|                      |    |
|----------------------|----|
| <b>U.S. Gallons:</b> | 15 |
|----------------------|----|

**CONSTRUCTION – (All thickness and weights reflect minimum requirements)**

|   |  |                   |          |
|---|--|-------------------|----------|
| <b>Sidewall:</b>                            | Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 1100 PSI Mullen. |                   |          |
| <b>Sidewall Adhesive:</b>                   | Sodium Silicate Between Each Lamination  |                   |          |
| <b>Lining:</b>                              | Heavy Duty Polyethylene  |                   |          |
| <b>Barrier:</b>                             | N/A  |                   |          |
| <b>Bottom:</b>                              | .220"/1300# PSI Heading (Thickness/Test)   |                   |          |
| <b>Chime Band Top:</b>                      | Galvanized Steel   | <b>Width:</b>     | Standard |
| <b>Chime Band Bottom:</b>                   | Galvanized Steel   | <b>Width:</b>     | Wide     |
| <b>Closure:</b>                             | Galvanized Steel   |                   |          |
| <b>Cover Type:</b>                          | Plastic  |                   |          |
| <b>Gasket:</b>                              | Urethane   |                   |          |
| <b>Fittings:</b>                            | N/A  | <b>Diaphragm:</b> | N/A      |
| <b>Additional Construction Information:</b> | N/A  |                   |          |

**TREATMENT**

|                          |                    |                             |     |
|--------------------------|--------------------|-----------------------------|-----|
| <b>Exterior Finish:</b>  | Plain Kraft        | <b>Paint or Skin Color:</b> | N/A |
| <b>Print:</b>            | N/A                |                             |     |
| <b>Print Color:</b>      | N/A                |                             |     |
| <b>Poly Bag:</b>         | N/A                | <b>Bag Option:</b>          | N/A |
| <b>Misc. Treatments:</b> | Alcohol Spray Test |                             |     |

**Special Instructions:** Certificate stamp on sidewall

**MARKINGS**

|                               |      |
|-------------------------------|------|
| <b>Mfg Certificate Stamp:</b> | 400# |
|-------------------------------|------|

NOTE: All dimensions listed on the above drum are nominal. Kraft paper is subject to change with variances in relative humidity. Diameters can vary +/- 1/16". Height to variances can vary +/- 1/4" per ft. of drum sidewall. All thicknesses and other dimensions are nominal unless otherwise stated.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG31135

DESCRIPTION:

15 Gallon Kraft Fiber Open Head Drum, Natural Plastic Cover, Lok-Rim, Liquidpak