

30 gal Open Head Kraft Fiber Drum with 2" Buttress and 3/4" NPS Fittings

MAUSER USA SPEC (185010)	18-30-400 LR LP6 PCGBVO
GALLON CAPACITY	30
INSIDE DIMENSIONS ... (DIAMETER X HEIGHT)	18 1/2 x 28
OUTSIDE DIMENSIONS ... (DIAMETER X HEIGHT)	19 3/8 x 29
TARE WEIGHT	11.8 Lbs.
SIDEWALL	GRADE 55# Linerboard
	BARRIER OR LINER 6 mil LLDPE
	PLYS 8 Plys Total
	TEST (PSI) 900 Lbs.
PACKAGING WEIGHT LIMIT	400 Lbs.
BOTTOM HEAD ELEMENT	TYPE Laminated Fibre
	CALIPER 200
	MULLEN 1200
	BARRIER OR LINER 6 mil LLDPE
BOTTOM CHIME	TYPE Steel
	GAUGE 24 Ga.
	FINISH Electro Galvanized
COVER OR TOP HEAD	TYPE HDPE (B&V)
	GAUGE 90 mil
	FINISH Natural
TOP CHIME	TYPE Steel
	GAUGE 24 Ga.
	FINISH Electro Galvanized
CLOSURE	TYPE Loc Ring (Steel)
	GAUGE 24 Ga.
	FINISH Electro Galvanized
CAPACITY IN CUBIC INCHES	8,085
CAPACITY IN CUBIC FEET	4.67
ADDITIONAL FEATURES	Adiprene seal in bottom chime and heat seal tape over inside seam.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: