# 31.5 gal Open Head Kraft Fiber Drum

## CONFORMS WITH REGULATIONS

NMFC:	Item 291	
UN:	1G/Y200/S	

### NOMINAL DIMENSIONS

Inside Diameter:	18-1/2"	
Inside Height:	27-1/4"	
Outside Height:	28-1/4"	
Tare Weight (approx):	12.8#	
Net Packing Weight:	550#	

#### NOMINAL CAPACITY

U.S. Gallons:	31.5

CONSTRUCTION - (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 1000 PSI Mullen.		
Sidewall Adhesive:	Sodium Silicate Between Each Lamination		
Lining:	N/A		
Barrier:	N/A		
Bottom:	.220"/1100# PSI Heading (Thickness/Test)		
Chime Band Top:	Galvanized Steel	Width:	Wide
Chime Band Bottom:	Galvanized Steel	Width:	Wide
Closure:	Galvanized Steel		
Cover Type:	24 Ga Steel		
Gasket:	N/A		
Fittings:	N/A	Diaphragm:	N/A
Additional Construction Information:	N/A		le a construire

## TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option: N	/A
Misc. Treatments:	N/A	the state of the	

Special Instructions: Certificate stamp on sidewall with customer specification number below

DISCLAIMER	DISTRIBUTED BY: 🔞	EF NO.:
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT	<b>ipeline</b> Packaging	
THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.	DESCRIPTION:	

## MARKINGS

Mfg Certificate Stamp: 550#