



| | | | |
|------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|---------------------------------------------|
| | | Product Name: P-15 | |
| Regulatory Information: un 1H1/Y1.9/100 (Test Report P110) un 1H1/Y1.3/100 with vent (Test Report P109) | Bill of Materials: Body: P-15, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Fittings: 2" and 3/4" NPS. Vented bungs are available as an option. (NPS = National Pipe Straight thread) | Product Illustration:  | |
| Nominal Capacity: 15.0 U.S. Gallons | Outage: 2.2 U.S. Gallons | Overall Height: 26.3 inches | Total Weight: 8.5 lbs. |
| Actual Capacity: 17.2 U.S. Gallons | Outage %: 14.5 % | Body Height: 26.3 inches | Body Weight: 8.5 lbs. |
| Export Cubes: 2.95 cu. ft. | Nominal O.D.: 14.4 inches | Mid Panel Height: 14.8 inches | Min. Wall Thickness: 0.110 inches |
| Special Notes: | | | |

- 1) Maximum filling temperature ~160°F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum.
- 2) Drums may be stacked 4 high (1+3) maximum with pallets between drums. For nonvented drums, maximum top load on bottom drums not to exceed 1000 lbs each. For vented drums, maximum top load on bottom drums not to exceed 500 lbs each. Pallets should be of good quality that provides adequate support for plastic drums.
- 3) Volume markers available.
- 4) Recycle symbol embossed on bottom.
- 5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.

| | |
|----------------------------------------------------------------------------------------------------------|----------------------|
| DISTRIBUTED BY:  | REF NO.: DWG30188 |
| DESCRIPTION: 15 Gallon Natural TH Drum | |

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.