



- CLOSURE NOTES:**
1. APPLICATION TORQUE: 10-18 IN. LBS
 2. "T" & "E" ARE THE AVERAGE OF 2 MEASUREMENTS TAKEN APPROXIMATELY 90° APART
 3. "T" IS TAKEN TOWARD THE BOTTOM OF THE CLOSURE JUST BELOW THE START OF THE FULL THREAD
 4. THE "E" DIAMETER IS TAKEN AS CLOSE TO THE INSIDE DECK AS POSSIBLE

DOSAGE OPTIONS	
190mcl	160mcl
140mcl	90mcl

LINER OPTIONS	
PE	EVA
POLYBUTYL	F-217

SPRING OPTIONS	
SS	NITRONIC

No.	Part Name	Mat'l
1	HOOD	PP
2	ACTUATOR	PP
3	INSERT	ACETAL
4	PISTON	PE
5	TURRET	PP
6	POPPET	PE
7	LINER	SEE TABLE
8	BODY	PP
9	SEAL VALVE	PE
10	SPRING	SEE TABLE
11	CLOSURE	PP
12	DIPTUBE	PE

- 1 DIMENSIONS IN BRACKETS ARE IN MILLIMETERS
- 2 TOLERANCE FOR ORIFICES LESS THAN .060" [1,52 MM] DIA.: ±.002" [0,05 MM]
- 3 ALL OTHER TOLERANCES ±.005" [0,13 MM] UNLESS OTHERWISE SPECIFIED

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: