



- 1 NOZZLE  
(HIGH DENSITY POLYETHYLENE)
- 2 DISCHARGE VALVE  
(MED. DENSITY POLYETHYLENE)
- 3 VALVE BODY  
(POLYPROPYLENE)
- 4 PISTON  
(MED. DENSITY POLYETHYLENE)
- 5 SPRING  
(STAINLESS STEEL)
- 6 SHROUD - ERGO  
(POLYPROPYLENE)
- 7 BALL VALVE  
(GLASS, PLASTIC, STAINLESS STEEL)
- 8 TUBE RETAINER  
(POLYPROPYLENE)
- 9 GASKET  
(POLYETHYLENE FOAM)
- 10 CLOSURE 28-400  
(POLYPROPYLENE)
- 11 DIP TUBE  
(POLYPROPYLENE)
- 12 TRIGGER  
(POLYPROPYLENE)

BECAUSE THE CLOSURE HAS A 1/2° DRAFT:

THE MAX \*T\* DIA OF 28.19[1.110] IS  
TAKEN AT THE BOTTOM OF THE CLOSURE

THE MIN \*T\* DIA OF 27.66[1.089] IS  
TAKEN AT 16.66[.656] FROM THE BOTTOM  
OF THE CLOSURE

THE MAX \*E\* DIA OF 25.81[1.016] IS  
TAKEN AT THE FIRST FULL THREAD

THE MIN \*E\* DIA OF 25.27[0.995] IS  
TAKEN AT 16.66[.656] FROM THE BOTTOM  
OF THE CLOSURE

**"UNCONTROLLED"**

**DISCLAIMER**

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



DWG NO.:

DWG10082

DESCRIPTION:

28-400 Trigger Sprayer