

16.5 gal Open Head Kraft Fiber Drum

CONFORMS WITH REGULATIONS

NMFC:	Item 291
UN:	1G/X60/S

NOMINAL DIMENSIONS

Inside Diameter:	14"
Inside Height:	24-7/8"
Outside Height:	25-7/8"
Tare Weight (approx):	6.9#
Net Packing Weight:	225#

NOMINAL CAPACITY

U.S. Gallons:	16.5
---------------	------

CONSTRUCTION – (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 700 PSI Mullen.		
Sidewall Adhesive:	Sodium Silicate Between Each Lamination		
Lining:	N/A		
Barrier:	N/A		
Bottom:	.120"/1000# PSI Heading (Thickness/Test)		
Chime Band Top:	Galvanized Steel	Width:	Standard
Chime Band Bottom:	Galvanized Steel	Width:	Standard
Closure:	Galvanized Steel		
Cover Type:	26 Ga Steel – Interlocking		
Gasket:	N/A		
Fittings:	N/A	Diaphragm:	N/A
Additional Construction Information:	N/A		

TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	N/A		

Special Instructions: N/A

MARKINGS

Mfg Certificate Stamp:	225#
------------------------	------



Pipeline Packaging

30310 Emerald Valley Pkwy
Glenwillow, OH 44139

PPC ITEM NUMBER:	85040	SKU:	03-03-048-00028		
DRAWN BY:	-	CHECKED BY:	-		
		DATE:	3/13/2019		
DESCRIPTION:	16.5 Gal Open Head Fiber Drum		COLOR:	Kraft	
PART MATERIAL:	-	VOLUME:	-	WEIGHT:	-
DWG NO.:	-	DWG SIZE:	A	SHEET NO:	1 of 1
				REV:	-

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing