CONFORMS WITH REGULATIONS

NMFC:	Item 291
UN:	1G/X50/S

NOMINAL DIMENSIONS

Inside Diameter:	15-1/2"	
Inside Height:	26-1/2*	
Outside Height:	27-1/2"	
Tare Weight (approx):	7.0#	
Net Packing Weight:	225#	

NOMINAL CAPACITY

U.S. Gallons:	21.5	
the second se	the second se	

CONSTRUCTION - (AI thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 700 PSI Mullen.			
Sidewall Adhesive:	Sodium Silicate Between Each Lamination			
Lining:	N/A			
Barrier:	N/A			
Bottom:	.120"/1000# PSI Heading (Thickness/Test)			
Chime Band Top:	Galvanized Steel	Width:	Standard	
Chime Band Bottom:	Galvanized Steel	Width:	Standard	
Closure:	Galvanized Steel			
Cover Type:	Plastic	1816 - T		
Gasket:	Urethane			
Fittings:	N/A	Diaphragm:	N/A	
Additional Construction Information:	N/A			

TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin C	olor: N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	N/A		

Special Instructions: Certificate stamp on sidewall with customer spec fication number below

MARKINGS

Mfg Certificate Stamp:	225#
------------------------	------

Pipeline Packaging		30310 Emerald Valley Pkwy Suite #500 Glenwillow, OH 44139			
PPC Item Number:		SKU:			
DRAWN BY: D. Grace	CHECKE		Ashinge	DATE:	4/12/2018
DESCRIPTION:			С	OLOR:	
PART MATERIAL:	VOLUN	ME:		WEIGHT:	
DWG NO.:	DWG	SIZE: A	SHEET	NO: 1 of 1	REV: _

PROPRIETARY AND CONFIDENTIAL	UNLESS OTHERWISE SPECIFIED:	DESCRIPTION
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOL PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION I		PART MATER
PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.	TOLERANCES: Specified in drawing	DWG NO.: