30 gal Open Head Kraft Fiber Drum with 2" Buttress and 3/4" NPS Fittings

MAUSER USA SPEC (185010)		18-30-400 LR LP6 PCGBVO
GALLON CAPACITY		30
INSIDE DIMENSIONS … (DIAMETER X HEIGHT)		18 1/2 x 28
OUTSIDE DIMENSIONS …(DIAMETER X HEIGHT)		19 3/8 x 29
TARE WEIGHT		11.8 Lbs.
SIDEWALL	GRADE	55# Linerboard
	BARRIER OR LINER	6 mil LLDPE
	PLYS	8 Plys Total
	TEST (PSI)	900 Lbs.
PACKAGING WEIGHT LIMIT		400 Lbs.
BOTTOM HEAD ELEMENT	TYPE	Laminated Fibre
	CALIPER	.200
	MULLEN	1200
	BARRIER OR LINER	6 mil LLDPE
BOTTOM CHIME	TYPE	Steel
	GAUGE	24 Ga.
	FINISH	Electro Galvanized
COVER OR TOP HEAD	TYPE	HDPE (B&V)
	GAUGE	90 mil
	FINISH	Natural
TOP CHIME	TYPE	Steel
	GAUGE	24 Ga.
	FINISH	Electro Galvanized
CLOSURE	TYPE	Loc Ring (Steel)
	GAUGE	24 Ga.
	FINISH	Electro Galvanized
CAPACITY IN CUBIC INCHES		8,085
CAPACITY IN CUBIC FEET		4.67
ADDITIONAL FEATURES		Adiprene seal in bottom chime and heat seal tape over inside seam.

Pipeline Packaging
30310 Emerald Valley Pkwy
Glenwillow, OH 44139

PPC ITEM NUMBER: 85032	SKU: 03-03-048-00042	
DRAWN BY: -	CHECKED BY: -	DATE: 3/13/2019
DESCRIPTION: 30 Gal Open Head Fiber Drum		COLOR: Kraft
PART MATERIAL: -	VOLUME: -	WEIGHT: -
DWG NO.: -	DWG SIZE: A	SHEET NO: 1 of 1 / REV: -

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing