

55 gal Open Head Kraft Fiber Drum with 2" Buttress and 3/4" NPS Fittings

CONFORMS WITH REGULATIONS

NMFC:	Item 296 – Liquid 2A
UN:	N/A

NOMINAL DIMENSIONS

Inside Diameter:	21-1/2"
Inside Height:	37-1/16"
Outside Height:	38-1/16"
Tare Weight (approx):	21.3#
Net Packing Weight:	600#

NOMINAL CAPACITY

U.S. Gallons:	55
---------------	----

CONSTRUCTION – (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 1200 PSI Mullen.		
Sidewall Adhesive:	Sodium Silicate Between Each Lamination		
Lining:	Heavy Duty Polyethylene		
Barrier:	N/A		
Bottom:	.240"/1500# PSI Heading (Thickness/Test)		
Chime Band Top:	Galvanized Steel with Stainless Steel Overlay	Width:	Standard
Chime Band Bottom:	Galvanized Steel	Width:	Wide
Closure:	Galvanized Steel		
Cover Type:	Plastic		
Gasket:	Urethane		
Fittings:	2" Bung & 3/4" Vent	Diaphragm:	Removed
Additional Construction Information:	N/A		

TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	N/A		

Special Instructions: N/A



Pipeline Packaging

30310 Emerald Valley Pkwy
Glenwillow, OH 44139

PPC ITEM NUMBER: 85000	SKU: 03-03-048-00070		
DRAWN BY: -	CHECKED BY: -	DATE: 3/13/2019	
DESCRIPTION: 55 Gal Open Head Fiber Drum	COLOR: Kraft		
PART MATERIAL: -	VOLUME: -	WEIGHT: -	
DWG NO.: -	DWG SIZE: A	SHEET NO: 1 of 1	REV: -

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing