55 gal Open Head Kraft Fiber Drum with 2" Buttress and 3/4" NPS Fittings

CONFORMS WITH REGULATIONS

NMFC:	Item 296 – Liquid 2A
UN:	N/A

NOMINAL DIMENSIONS

Inside Diameter:	21-1/2"
Inside Height:	37-1/16"
Outside Height:	38-1/16"
Tare Weight (approx):	21.3#
Net Packing Weight:	700#

NOMINAL CAPACITY

	U.S. Gallons:	55
--	---------------	----

CONSTRUCTION - (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting or exceeding minimum			
	thickness requirements of 1200 PSI Mullen.			
Sidewall Adhesive:	Sodium Silicate Between Each Lamination			
Lining:	Heavy Duty Polyethylene			
Barrier:	N/A			
Bottom:	.240"/1500# PSI Heading (Thickness/Test)			
Chime Band Top:	Galvanized Steel	Width:	Wide	
Chime Band Bottom:	Galvanized Steel	Width:	Wide	
Closure:	Galvanized Steel			
Cover Type:	Plastic			
Gasket:	Urethane			
Fittings:	2" & 3/4" Plugs	Diaphragm:	Removed	
Additional Construction				
Information:	N/A			

TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Colo	r: N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	Alcohol Spray Test		

Special Instructions: Certificate stamp on sidewall

MARKINGS Mfg Certificate Stamp: 700#		30310 Emerald Valley Pkwy Glenwillow, OH 44139			
		PPC ITEM NUMBER: 85129		SKU: 03-03-048-00075	
		DRAWN BY: -	CHECKED BY:	_	DATE: 3/14/2019
PROPRIETARY AND CONFIDENTIAL	UNLESS OTHERWISE SPECIFIED:	DESCRIPTION: 55 Gal Ope	en Head Fiber [DLOR: Kraft
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN	UNITS OF MEASURE: Inches	PART MATERIAL:	VOLUME:	-	WEIGHT: -
PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.	TOLERANCES: Specified in drawing	DWG NO.:	DWG SIZE:	SHEET N	NO: REV: 1 of 1