

**CONFORMS WITH REGULATIONS**

<b>NMFC:</b>	Item 296 – Liquid 2A
<b>UN:</b>	N/A

**NOMINAL DIMENSIONS**

<b>Inside Diameter:</b>	21-1/2"
<b>Inside Height:</b>	37-1/16"
<b>Outside Height:</b>	38-1/16"
<b>Tare Weight (approx):</b>	19#
<b>Net Packing Weight:</b>	600#

**NOMINAL CAPACITY**

<b>U.S. Gallons:</b>	55
----------------------	----

**CONSTRUCTION – (All thickness and weights reflect minimum requirements)**

<b>Sidewall:</b>	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 1200 PSI Mullen.		
<b>Sidewall Adhesive:</b>	Sodium Silicate Between Each Lamination		
<b>Lining:</b>	Heavy Duty Polyethylene		
<b>Barrier:</b>	N/A		
<b>Bottom:</b>	.240"/1500# PSI Heading (Thickness/Test)		
<b>Chime Band Top:</b>	Stainless Steel	<b>Width:</b>	Standard
<b>Chime Band Bottom:</b>	Galvanized Steel	<b>Width:</b>	Wide
<b>Closure:</b>	Galvanized Steel		
<b>Cover Type:</b>	Plastic		
<b>Gasket:</b>	Urethane		
<b>Fittings:</b>	2" & 3/4" Plugs	<b>Diaphragm:</b>	Removed
<b>Additional Construction Information:</b>	N/A		

**TREATMENT**

<b>Exterior Finish:</b>	Plain Kraft	<b>Paint or Skin Color:</b>	N/A
<b>Print:</b>	N/A		
<b>Print Color:</b>	N/A		
<b>Poly Bag:</b>	N/A	<b>Bag Option:</b>	N/A
<b>Misc. Treatments:</b>	Alcohol Spray Test		

**MARKINGS**

<b>Mfg Certificate Stamp:</b>	600#
-------------------------------	------



**Pipeline Packaging**

30310 Emerald Valley Pkwy  
Glenwillow, OH 44139

<b>PPC ITEM NUMBER:</b> 85137		<b>SKU:</b> 03-03-048-00076	
<b>DRAWN BY:</b> -	<b>CHECKED BY:</b> -	<b>DATE:</b> 3/14/2019	
<b>DESCRIPTION:</b> 55 Gal Open Head Fiber Drum		<b>COLOR:</b> Kraft	
<b>PART MATERIAL:</b> -	<b>VOLUME:</b> -	<b>WEIGHT:</b> -	
<b>DWG NO.:</b> -	<b>DWG SIZE:</b> A	<b>SHEET NO:</b> 1 of 1	<b>REV:</b> -

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

**UNLESS OTHERWISE SPECIFIED:**

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing