

CONFORMS WITH REGULATIONS

NMFC:	Item 291
UN:	1G/Y250/S

NOMINAL DIMENSIONS

Inside Diameter:	23"
Inside Height:	37-1/4"
Outside Height:	38-1/4"
Tare Weight (approx):	19.5#
Net Packing Weight:	550#

NOMINAL CAPACITY

U.S. Gallons:	67
----------------------	----

CONSTRUCTION – (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 1000 PSI Mullen.		
Sidewall Adhesive:	Sodium Silicate Between Each Lamination		
Lining:	N/A		
Barrier:	N/A		
Bottom:	.220"/1100# PSI Heading (Thickness/Test)		
Chime Band Top:	Galvanized Steel	Width:	Standard
Chime Band Bottom:	Galvanized Steel	Width:	Wide
Closure:	Galvanized Steel		
Cover Type:	24 Ga Steel		
Gasket:	Flowed In		
Fittings:	N/A	Diaphragm:	N/A
Additional Construction Information:	N/A		

TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	4 Mil Antistat	Bag Option:	Loose in drum
Misc. Treatments:	N/A		

Special Instructions: N/A**MARKINGS**

Mfg Certificate Stamp:	550#
-------------------------------	------



PPC Item Number:	SKU:
DRAWN BY: D. Grace	CHECKED BY: B. Ashinger
DATE: 4/12/2018	

DESCRIPTION:	COLOR:
PART MATERIAL:	VOLUME:
WEIGHT:	
DWG NO.: -	DWG SIZE: A
SHEET NO.: 1 of 1	REV.: -

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing