



30 gal Open Head Blue Plastic Drum with 3/4" EPDM

Product Specification Number: PSO30X-XX-XX-XX-XX-XX		Product Name: <b style="font-size: 1.2em;">OS-30			
Regulatory Information:	Bill of Materials:	Product Illustration:			
un 1H2/X150/S ¹ (Test Report P245)	Body: OS-30, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)				
un 1H2/X125/S ² (Test Report P244)					
un 1H2/Y180/S ³ (Test Report P246)					
UN 1H2/Y260/S (Test report P402, note 9)					
UN 1H2/Y100/S (Test report P236)					
Lockband: Side lever (SLL), Bolt and plastic.					
Nominal Capacity: 30.0 U.S. Gallons	Outage: 2.2 U.S. Gallons	Opening I.D.: 17.5 inches	Total Weight: 14.6 lbs.		
Actual Capacity: 32.2 U.S. Gallons	Outage %: 7.3 %	Nominal O.D.: 19.3 inches	Body Weight: 11.3 lbs.		
Export Cubes: 6.05 cu. ft.	Overall Height: 29.4 inches	Min. Wall Thickness: 0.125 inches	Chime Height: 0.530 inches		
Min. Blocking Diameter: 18.7 inches	Body Height: 29.1 inches	Mid Panel Height: 11.4 inches			
Special Notes:					
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top; padding: 5px;"> 1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability. 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 600 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Recycle symbol embossed on bottom. </td> <td style="width: 50%; vertical-align: top; padding: 5px;"> 5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 6) Manufactured at the following locations: ¹ Houston, with heavyweight cover ² Houston, with lightweight cover ³ Houston, Hazleton and Lockport with lightweight cover 7) Lockport weight is body / assembled 10.7/14.0 lbs nominal 8) Hazleton weight is body / assembled 10.4/13.7 lbs nominal 9) Available only from Lockport with total drum weight 15.3 lbs. </td> </tr> </table>				1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability. 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 600 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Recycle symbol embossed on bottom.	5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 6) Manufactured at the following locations: ¹ Houston, with heavyweight cover ² Houston, with lightweight cover ³ Houston, Hazleton and Lockport with lightweight cover 7) Lockport weight is body / assembled 10.7/14.0 lbs nominal 8) Hazleton weight is body / assembled 10.4/13.7 lbs nominal 9) Available only from Lockport with total drum weight 15.3 lbs.
1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability. 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 600 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Recycle symbol embossed on bottom.	5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 6) Manufactured at the following locations: ¹ Houston, with heavyweight cover ² Houston, with lightweight cover ³ Houston, Hazleton and Lockport with lightweight cover 7) Lockport weight is body / assembled 10.7/14.0 lbs nominal 8) Hazleton weight is body / assembled 10.4/13.7 lbs nominal 9) Available only from Lockport with total drum weight 15.3 lbs.				

		30310 Emerald Valley Pkwy Glenwillow, OH 44139	
PPC ITEM NUMBER: 80194		SKU: 03-14-048-00045	
DRAWN BY: -	CHECKED BY: -	DATE: 2/19/2019	
DESCRIPTION: 30 Gal Open Head Plastic Drum		COLOR: Blue	
PART MATERIAL: -	VOLUME: -	WEIGHT: -	
DWG NO.: -	DWG SIZE: A	SHEET NO: 1 of 1	REV: -

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing