## 55 gal Open Head Natural Plastic Drum with 2" and 2" Fittings

| Product Specification Number: PSA55X-XX-XX-XX-XX                             |   | Product Name: OS-55A  |               |
|--|---|-----------------------|---------------|
| Regulatory Information:  | Bill of Materials:  | Product Illustration: |               |
| un 1H2/X300/S - with 14 gauge bolt lockband (Test Report P251) un 1H2/Y250/S | Body: OS-55A, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)  |                       |               |
| (Test Report P252)   | Cover: Plain, one 2" opening, or two 2" openings available, NPS bungs, HDPE. Vented bungs are available as an option. (NPS = National Pipe Straight thread) |                       |               |
|  | Lockband:<br>Side lever (SLL) or Bolt   |                       |               |
| Nominal Capacity:  | Outage:   | Opening I.D.:         | Total Weight: |
| 55.0 U.S. Gallons  | 2.7 U.S. Gallons  | 19.3 inches           | 24.3 lbs.     |
| Actual Capacity:   | Outage %:   | Nominal O.D.:         | Body Weight:  |
| 57.7 U.S. Gallons  | 5.0 %   | 23.2 inches           | 19.6 lbs.     |
| Export Cubes:  | Overall Height:   | Min. Wall Thickness:  | Chime Height: |
| 11.02 cu. ft.  | 36.8 inches   | 0.090 inches          | 0.480 inches  |
| Min. Blocking Diameter:  | Body Height:  | Mid Panel Height:     |               |
| 22.2 inches  | 36.5 inches   | 11.5 inches           |               |
| Special Notes:   |   |                       | -             |

- 1) Maximum filling temperature 150 F. When filled 3) at this recommended maximum filling temperature 4) drums should be allowed to cool to ambient prior 5) to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.
- Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1300 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums.
- Handle with parrotbeak, side grabber, and sling.
- Recycle symbol embossed on bottom. Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.

lineline Packaging

30310 Emerald Valley Pkwy Glenwillow, OH 44139

| · · · · · · · · · · · · · · · · · · · |             |                 |           |  |  |
|---------------------------------------|-------------|-----------------|-----------|--|--|
| PPC ITEM NUMBER:                      |             | SKU:            |           |  |  |
| 80179                                 | )           | 03-14-048-00090 |           |  |  |
| DRAWN BY:                             | CHECKED BY: |                 | DATE:     |  |  |
| -                                     |             | -               | 2/19/2019 |  |  |
| DESCRIPTION:                          | •           | <u></u>         | OI OR:    |  |  |

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

## **UNLESS OTHERWISE SPECIFIED:**

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing

DWG NO .:

55 Gal Open Head Natural Drum **VOLUME:** 

PART MATERIAL:

DWG SIZE: SHEET NO:

Α

WEIGHT:

REV: 1 of 1