


<b>Product Specification Number:</b> PMB20X-XX-XX-XX-XX-XX		<b>Product Name:</b> <b>O-20MB</b>			
<b>Regulatory Information:</b>  un 1H2/Y130/S (Test Report P212)  un 1H2/Y130/S (Test Report P283)		<b>Bill of Materials:</b>  <b>Body:</b> O-20MB, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)  <b>Cover:</b> Plain or Bung & Vent, HDPE. The B & V design has a 2" and a 3/4" NPS bung, with a vented 3/4" being available as an option. (NPS = National Pipe Straight thread)  <b>Lockband:</b> Side lever (SLL) or Bolt			
<b>Product Illustration:</b>					
<b>Nominal Capacity:</b> 20.0 U.S. Gallons	<b>Outage:</b> 0.2 U.S. Gallons			<b>Opening I.D.:</b> 15.6 inches	<b>Total Weight:</b> 10.0 lbs.
<b>Actual Capacity:</b> 20.2 U.S. Gallons	<b>Outage %:</b> 1.0 %			<b>Nominal O.D.:</b> 15.9 inches	<b>Body Weight:</b> 7.5 lbs.
<b>Export Cubes:</b> 3.91 cu. ft.	<b>Overall Height:</b> 30.5 inches			<b>Taper Height:</b> 19.3 inches	<b>Nesting Height:</b> 8.9 inches
<b>Min. Blocking Diameter:</b> 13.5 inches	<b>Body Height:</b> 30.1 inches			<b>Min. Wall Thickness:</b> 0.090 inches	<b>Chime Height:</b> 0.505 inches

**Special Notes:**

- |   |  |
|---|--|
| <p>1) Maximum filling temperature 150 degrees F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.</p> <p>2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 750 lbs. each. Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums.</p> | <p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Drums are fully nestable without airlocking.</p> <p>5) Recycle symbol embossed on bottom.</p> <p>6) Patent number 5,881,898 embossed on drum.</p> <p>7) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.</p> |
|---|--|



30310 Emerald Valley Pkwy  
Suite #500  
Glenwillow, OH 44139

PPC Item Number:		SKU:	
DRAWN BY: D. Grace		CHECKED BY: B. Ashinger	
DATE: 4/12/2018			
DESCRIPTION:		COLOR:	
PART MATERIAL:	VOLUME:	WEIGHT:	
DWG NO.:	DWG SIZE:	SHEET NO.:	REV.:
-	A	1 of 1	-

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.</p>	UNLESS OTHERWISE SPECIFIED:
	UNITS OF MEASURE: Inches
	TOLERANCES: Specified in drawing