



14 gal Open Head Nestable Black Plastic Drum

Product Specification Number: POX14X-XX-XX-XX-XX-XX		Product Name: O-14			
Regulatory Information: un 1H2/X65/S ¹ (Test Report P205LK) (Test Report P203HS) un 1H2/Y100/S ² (Test Report P204LK) (Test Report P304HS)	Bill of Materials: Body: O-14, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Cover: Plain or Bung & Vent, HDPE. The B & V design has a 2" and a ¾" NPS bung, with a vented ¾" being available as an option. (NPS = National Pipe Straight thread) Lockband: Side lever (SLL) or Bolt	Product Illustration: 			
Nominal Capacity: 14.0 U.S. Gallons	Outage: 0.9 U.S. Gallons	Opening I.D.: 13.7 inches	Total Weight: 8.2 lbs.		
Maximum Capacity: 14.9 U.S. Gallons	Outage %: 6.4 %	Nominal O.D.: 14.9 inches	Body Weight: 6.5 lbs.		
Export Cubes: 2.95 cu. ft.	Overall Height: 26.3 inches	Teper Height: 15.8 inches	Nesting Height: 9.4 inches		
Min. Blocking Diameter: 13.0 inches	Body Height: 25.9 inches	Min. Wall Thickness: 0.090 inches	Chime Height: 0.525 inches		
Special Notes:					
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top; border: none;"> 1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability. 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 750 lbs. each. May be stacked two (2) drums high per pallet with slip sheet of plywood between layers of drums with top load not exceeding the specified limit. </td> <td style="width: 50%; vertical-align: top; border: none;"> 2) Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Drums are fully nestable without airlocking. 5) Recycle symbol embossed on bottom. 6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 7) Manufactured at the following locations: * Houston and Lockport * Lockport </td> </tr> </table>				1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability. 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 750 lbs. each. May be stacked two (2) drums high per pallet with slip sheet of plywood between layers of drums with top load not exceeding the specified limit.	2) Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Drums are fully nestable without airlocking. 5) Recycle symbol embossed on bottom. 6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 7) Manufactured at the following locations: * Houston and Lockport * Lockport
1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability. 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 750 lbs. each. May be stacked two (2) drums high per pallet with slip sheet of plywood between layers of drums with top load not exceeding the specified limit.	2) Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Drums are fully nestable without airlocking. 5) Recycle symbol embossed on bottom. 6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 7) Manufactured at the following locations: * Houston and Lockport * Lockport				


**30310 Emerald Valley Pkwy
Glenwillow, OH 44139**

PPC ITEM NUMBER: 80216 **SKU:** 03-14-049-00016

DRAWN BY: - **CHECKED BY:** - **DATE:** 2/19/2019

DESCRIPTION: 14 Gal OH Nestable Plastic Drum **COLOR:** Black

PART MATERIAL: - **VOLUME:** - **WEIGHT:** -

DWG NO.: - **DWG SIZE:** A **SHEET NO:** 1 of 1 **REV:** -

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing