


30 gal Tight Head Natural Plastic Drum with 2" Buttress and 2" NPT Fittings

Product Specification Number: PGP30X-XX-XX-XX-XX-XX		Product Name: GP-30	
Regulatory Information: un 1H1/Y1.9/150 (Test Report P124) un 1H1/Y1.4/150 with vent (Test Report P123) un 1H1/Y1.4/100 (Test Report P126, note 7) un 1H1/Y1.9/150 (Test Report P139, note 8) un 1H1/Y1.4/100 (Test Report P122, note 9) un 1H1/Y1.8/150 (Test Report P143, note 10)	Bill of Materials: Body: GP-30, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Fittings: 2" BTR and 2" NPS. Vented bungs are available as an option. (BTR = Buttress, NPS = National Pipe Straight thread)	Product Illustration: 	
Nominal Capacity: 30.0 U.S. Gallons	Outage: 2.6 U.S. Gallons	Overall Height: 29.6 inches	Total Weight: 13.8 lbs.
Actual Capacity: 32.6 U.S. Gallons	Outage %: 8.7 %	Body Height: 29.6 inches	Body Weight: 13.6 lbs.
Export Cubes: 6.27 cu. ft.	Nominal O.D. : 19.5 inches	Mid Panel Height: 10.4 inches	Min. Wall Thickness: 0.090 inches

Special Notes:	
1) Maximum filling temperature 150 F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum. 2) Nonvented drums may be stacked 4 high (1+3) maximum with pallets between drums, maximum top load on bottom drums not to exceed 1500 lbs each. Vented drums may be stacked 3 high (1+2) maximum with pallets between drums, maximum top load on bottom drums not to exceed 700 lbs each. Pallets should be of good quality that provides adequate support for plastic drums.	3) Handle with parrotbeak, side grabber, and sling. 4) Available with or without weepholes (no weepholes standard). 5) Recycle symbol embossed on bottom. 6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 7) Test report P126 applicable to drums that have been produced with special resin for higher ESCR performance mfg. in Houston. 8) Test report P139 is produced in Lockport at 14.7 lbs from low density resin. 9) Test Report P122 mfg. in Lockport for higher ESCR performance. 10) Test Report P143 mfg. in Houston at a weight of 15.0 lbs.


Pipeline Packaging 30310 Emerald Valley Pkwy
 Glenwillow, OH 44139

PPC ITEM NUMBER: 80002	SKU: 03-14-079-00048
DRAWN BY: -	CHECKED BY: -
DATE: 2/19/2019	

DESCRIPTION: 30 Gal Tight Head Natural HDPE Drum		COLOR: -	
PART MATERIAL: -	VOLUME: -	WEIGHT: -	
DWG NO.: -	DWG SIZE: A	SHEET NO: 1 of 1	REV: -

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing