PRODUCT SPECIFICATION VUN SK 24/12 CR-3 AF

PRODUCT:	VUN SK 24/12 CR-3 AF: This is a two piece child resistant closure, plastic injected molded fitment consisting of a spout (UT) and a screw cap (SK).	NECK FINISH:	Bericap Finith Drawing: ENG-00-004987 a
DESCRIPTION:	Product Code: 53525: White W10 SK, natural UT. 53542: Red R28 SK, natural UT 53552: Black BK7 SK, natural UT 53584: Yellow Y6 SK, natural UT	PACKAGING:	BERICAP Corrugated box with no polyethylene bags inside. Number of closures per box: 2000 Pallet Size: 40" x 48" x 5" # of tier per pallet: 3 # of carton per tier: 6 # of carton per pallet: 18 # of closure per pallet: 34,000
RAW MATERIALS:	Screw cap (SK): Inco: HDPE T50-500-196		
	Color master batches: White, W10, Clariant 01EHD-580, @ 1% LDR Red, R28, PolyOne CC10146593 @ 1% LDR Black BK7, Clariant PE94720802 @ 1% LDR Yellow Y6, Clariant 03EHD-1236 @ 1% LDR	CHARACTERISTICS:	Two piece closure with child resistant feature
	Spout (UT): DOW LDPE 503A	PRODUCT USAGE:	Closure Application and Removal: • Insertion Force: 490.33 N (110.23 lb) to 735.49 N (165.34 lb) • Membrane Force: 55 N (12.36 lb) to 80 N (17.98 lb)
WEIGHT:	Combined weight: 6.1 g		Closure Storage: In a dry area Temperature: 20° C to 38° C. (68° C to 100° F)
DIMENSIONAL:	Drawing No: ENG-00-019014 d		Stacking carton: maximum of 2 pallet: high Optimum performance period: use within 12 months of manufacture.

