

## Nozzle

Note: actual spray or foam pattern is determined by the product being sprayed and the method of actuation (i.e. speed, frequency, ect.)

SOna Spray/Off narrow angle ~40° \\_ +/- 15° CR\* SOwa Spray/Off wide angle ~80° \\_ +/- 15° CR\* SOS Spray/Off/Stream ~40° \( +/- 15° / Jet Stream CR\* SOF Spray/Off/Foam Open: ~40° \L +/- 15° / Closed - Foam

FOnv Foam/Off non-vented CR\* FOvna Foam/Off vented narrow angle CR\* FOvwa Foam/Off vented wide angle CR\* FOvi Foam/Off vented insert CR\* FOvm Foam/Off vented mesh

Closure

28-400 "Standard Cap" 28-410 "Deep Cap" 28-410 Ratchet (U.S.) "Ratchet" 28-410 Lock Cap (Europe) Snap-On CR "Snap-On" / Snap-On Non-CR "Bayonet" 28-DIN "DIN Cap"

Trigger

2 Finger ("Short" / "Standard") or 3 Finger ("Long") (CR Nozzle Not Available with Long Trigger)

Output

≈ 1.20 cc or ≈ 1.35 cc

Shroud

(Reference Image Above) Custom Designs Available - Contact Sales Representative for Details

Dip Tube

Straight "V" Cut or Curved "V" Cut

**Optional Features** 

OpUs H&G (38mm cap, handle, 36" dip tube, tube filter & stainless steel tube weight) Upside-Down (USD) Version (not available in snap-on version / contains metal component)

Passive Venting (PV) Top Label Side Label

Colors

White, Natural, Opaque, Translucent & Custom Order Colors (reference price list for details on custom colors)

	Packaging
ipeline	Packaging

30310 Emerald Valley Pkwy Glenwillow, OH 44139

PPC ITEM NUMBER:	73244	ļ
DRAWN BY:		CHE

SKU: 05-16-074-00107 DATE:

COLOR:

CKED BY:

2/19/2019

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

## **UNLESS OTHERWISE SPECIFIED:**

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing

## DESCRIPTION:

28mm Sprayer PP Closure PART MATERIAL:

VOLUME: WEIGHT:

DWG NO.:

DWG SIZE: SHEET NO: Α

REV: 1 of 1