



- 1 NOZZLE
(HIGH DENSITY POLYETHYLENE)
- 2 DISCHARGE VALVE
(MED. DENSITY POLYETHYLENE)
- 3 VALVE BODY
(POLYPROPYLENE)
- 4 PISTON
(MED. DENSITY POLYETHYLENE)
- 5 SPRING
(STAINLESS STEEL)
- 6 SHROUD - ERGO
(POLYPROPYLENE)
- 7 BALL VALVE
(GLASS, PLASTIC, STAINLESS STEEL)
- 8 TUBE RETAINER
(POLYPROPYLENE)
- 9 GASKET
(POLYETHYLENE FOAM)
- 10 CLOSURE 28-400
(POLYPROPYLENE)
- 11 DIP TUBE
(POLYPROPYLENE)
- 12 TRIGGER
(POLYPROPYLENE)

BECAUSE THE CLOSURE HAS A 1/2° DRAFT:

THE MAX *T* DIA OF 28.19[1.110] IS TAKEN AT THE BOTTOM OF THE CLOSURE

THE MIN *T* DIA OF 27.66[1.089] IS TAKEN AT 16.66[.656] FROM THE BOTTOM OF THE CLOSURE

THE MAX *E* DIA OF 25.81[1.016] IS TAKEN AT THE FIRST FULL THREAD

THE MIN *E* DIA OF 25.27[0.995] IS TAKEN AT 16.66[.656] FROM THE BOTTOM OF THE CLOSURE

PER
CUSTOMER
ORDER
±1/16"



Pipeline Packaging

30310 Emerald Valley Pkwy
Glenwillow, OH 44139

PPC ITEM NUMBER:

73024

SKU:

05-16-074-00182

DRAWN BY:

CHECKED BY:

DATE:

2/18/2019

DESCRIPTION:

28-400 Sprayer PP Closure

COLOR:

-

PART MATERIAL:

VOLUME:

WEIGHT:

DWG NO.:

DWG SIZE:

SHEET NO:

REV:

A

1 of 1

-

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PIPELINE PACKAGING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PIPELINE PACKAGING IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

UNITS OF MEASURE: Inches

TOLERANCES: Specified in drawing