





## THREAD DETAIL 5 THREADS PER INCH 0.200" [5.06 PITCH

REFERENCE	TOLERANCE	DIMENSION	UNITS
E	±0.014 [0.35]	4.226 [107.34]	in [mm]
Т	±0.014 [0.35]	4.346 [110.39]	in [mm]
Н	±0.014 [0.35]	0.550 [13.97]	in [mm]
OAH	±0.014 [0.35]	0.675 [17.15]	in [mm]
OD	±0.014 [0.35]	4.480 [113.79]	in [mm]
PART WEIGHT	± 2.0	21.65	g

## PAGE 1 OF 2

<u>DISCLAIMER</u>
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:

ipeline Packaging

REF NO.:

DWG30302

**DESCRIPTION:** 

110-400 PP Matte Top, Ribbed Sides Cap with Heat Seal

Product	ISPVC-PET U10			
Scope	One piece foam backed heat induction foil innerseal that will provide a tamper evident welded seal to and PET containers.			
Composition	Material	Standard	Metric	
	PET Film	0.0005"	0.013mm	PET Film
	Polyolefin Foam	0.009"	0.229mm	Polyolefin Foam
	Foil	0.001"	0.025mm	Foil
	Heat Seal	0.0005"	0.013mm	Heat Seal

FDA Status: 21 CFR 177.1210 Drug Master File (DMF): 11485 EU / EP Reg.: GTR Oxygen: Essentially zero MVTR: Essentially zero

Print Location (if any): Top layer of PET film

PAGE 2 OF 2

**DISCLAIMER** 

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:

Recommended Storage and Handling: Refer to website

ipeline Packaging

REF NO.:

DWG30302

**DESCRIPTION:** 

110-400 PP Matte Top, Ribbed Sides Cap with Heat Seal