

Rated Capacity	275 Gallons	
Specific Gravity Maximum Rating	1.9 SG	
Maximum Fill Temperature	150° F	
Hydrostatic Pressure Rating	100 kPa in Cage	
Inner Receptacle	Blowmolded: HMWHDPE Resin: Greif GB3 Weight: 34 pounds nominal Length: 45.75 inches nominal Width: 38.0 inches nominal Height: 39.75 inches nominal Production leak-tested per 49 CFR 178.801(f) at 3 psi	
Top Closure	Type: 6" Cap with 2" Closure wit Vent – Tamper Evident	





Top Closure	Type: 6" Cap with 2" Closure with Ventix Vent – Tamper Evident Fabrication: Injection molded	Cap & Plug Material: PE Gasket(s): EPDM
Representative Service Equipment	Type: 2" Quick Disconnect Screwable Valve Material: Polypropylene	Collar Gasket: Viton (FKM) Valve Seal Gasket(s): EPDM
UN Qualification	Refer to UN test report for the structure it is installed into for proper UN marks	

DISTRIBUTED BY:

ipeline Packaging

DWG30433

REF NO.:

<u>DISCLAIMER</u>
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DESCRIPTION:

275 Gallon Remanufactured IBC Tote, New Bottle