





SECTION A-A

<u>THREAD DETAILS:</u> 6 THREADS PER INCH, 0.167" PITCH					
REFERENCE	TOLERANCE	UNITS DIMENSION			
E	± 0.010 [0.25]	in [mm]	1.010 [25.65]		
Т	± 0.010 [0.25]	in [mm]	1.095 [27.81]		
н	± 0.010 [0.25]	in [mm]	0.390 [9.91]		
OAH	± 0.010 [0.25]	in [mm]	0.445 [11.30]		
OD	± 0.010 [0.25]	in [mm]	1.205 [30.61]		
PART WEIGHT	±0.15	g	1.93		

Page 1 of 2	THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING	DISTRIBUTED B	Y: Pipeline Packaging	REF NO.: DWG30351
		DESCRIPTION:	28-400 White PP Smooth with FS319.20 Plain Liner	

P

Product	.020" Pulp FS 3-	19				
Scope	Two piece pulp backed heat induction foil innerseal that will provide an aggressive bond with clean peel removal from PET and PVC containers. (Not recommended for use on CPET. Easy access / "puncture foil" when wax bonded to pulp.)					
Composition	Material	Standard	Metric			
	Backing	.020"	.508 mm	Backing		
	Wax	-	-	Wax		
	Foil	.001"	.0254mm	\$		
	Heat Seal	.0005"	.0127mm	Foil Heat Seal		
				Adhesive or resin bonding layers not shown.		
FDA Status: 21 CFR 177.1210		Recommend	Recommended Storage and Handling: Refer to Website			
Drug Master File (DMF): #4544 EU / EP Reg.:		:				
GTR Oxygen: Essentially Zero MVTR: Essentially Zero						
Print Location (if any)	: Foil Layer and/or	Heat Seal Layer				

Page 2 of 2	THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING	DISTRIBUTED B	Y: Peline Packaging	REF NO.: DWG30351
		DESCRIPTION:	28-400 White PP Smooth with FS319.20 Plain Line	•