



CONFORMS WITH REGULATIONS

| | |
|--------------|-----------|
| NMFC: | Item 291 |
| UN: | 1G/X120/S |

NOMINAL DIMENSIONS

| | |
|------------------------------|---------|
| Inside Diameter: | 18-1/2" |
| Inside Height: | 30-1/4" |
| Outside Height: | 31-1/4" |
| Tare Weight (approx): | 12.7# |
| Net Packing Weight: | 400# |

NOMINAL CAPACITY

| | |
|----------------------|----|
| U.S. Gallons: | 35 |
|----------------------|----|

CONSTRUCTION – (All thickness and weights reflect minimum requirements)

| | | | |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------|-------------------|----------|
| Sidewall: | Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 900 PSI Mullen. | | |
| Sidewall Adhesive: | Sodium Silicate Between Each Lamination | | |
| Lining: | N/A | | |
| Barrier: | N/A | | |
| Bottom: | .220"/1100# PSI Heading (Thickness/Test) | | |
| Chime Band Top: | Galvanized Steel | Width: | Standard |
| Chime Band Bottom: | Galvanized Steel | Width: | Standard |
| Closure: | Galvanized Steel | | |
| Cover Type: | 24 Ga Steel | | |
| Gasket: | Flowed In | | |
| Fittings: | N/A | Diaphragm: | N/A |
| Additional Construction Information: | N/A | | |

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG30404

DESCRIPTION:

35 Gallon Fiber Lok-Rim Drum with Metal Cover