Regulatory Information:

Bill of Materials:

Product Illustration:

un 1H1/Y1.9/150 (Test Report P138)

Body:

GP-55FRRH, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)

Fittings:

2" BTR and 2" NPS.
Double Buttress
configuration available.
(BTR = Buttress,
NPS = National Pipe
Straight thread)



Nominal Capacity:	Outage:	Overall Height:	Total Weight:
55.0 U.S. Gallons	2.4 U.S. Gallons	35.4 inches	22.7 lbs.
Maximum Capacity:	Outage %:	Body Height:	Body Weight:
57.43 U.S. Gallons	4.4 %	35.4 inches	22.5 lbs.
Export Cubes:	Nominal O.D.:	Mid Panel Height:	Min. Wall Thickness:
10.71 cu. ft.	23.3 inches	11.7 inches	0.140 inches

Special Notes:

- Maximum filling temperature 150 F for all foods 3) and other FDA regulated substances. 160 F for all 4) non-foods and other substances that are not 5) regulated by FDA. When filled at these 6) recommended maximum filling temperatures drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.
- 2) Drums may be stacked 3 high (1+2) maximum with pallets between drums. For nonvented drums, maximum top load on bottom drums not to exceed 2000 lbs each. Pallets should be of good quality that provides adequate support for plastic drums.

-) Handle with parrotbeak, side grabber, and sling.
-) Fits four wide in standard trailer.
- 5) Recycle symbol embossed on bottom.
- Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.

DISTRIBUTED BY:

ipeline Packaging

DIMON

REF NO.:

DWG30473

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DESCRIPTION:

55 Gallon Black Plastic Tight Head Drum