Factory seconds

Dimensions

(A) Fitting Centers	17.5"	
(B) Outside Diameter (+/- 1/16")	23.0"	
(C) Inside Diameter (+/- 1/16")	22.5"	
(D) Height (+/- 1/8")	34 3/4"	
Weight (+/-3%)	32.6 lb	

<u>Material</u>

Head	1.0 mm CRCQ Steel
Body	0.8 mm CRCQ Steel
Bottom	1.0 mm CRCQ Steel

*All Steel tolerances conform to ISO3574

Head Fittings

Flanges	2"+3/4" TS Plated with Buna gasket
Plugs	2"+3/4" TS Plated with Buna gasket
Capseals	3/4" TS metal cramping white plastic

Closing Ring

Ring	NA
Bolt, Nut	NA
Gasket	NA
Interior	

	Coating	Varies
1	-	

Exterior Coating

Тор	Any
A Panel	Any
B Panel	Anv
C Panel	Any
Bottom	Any

<u>Silkscreen</u>	No				
<u>Embossing</u>	UN 1A1/X1.8/300	1.0/0.8/1.0			
<u>Inkjet</u>	UN 1A1/X1.8/300	M-4601	43Y327	JD	

	DISTRIBUTED BY:	REF NO.:	
		DWG30914	
DISCLAIMER	lipeline Packaging		
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING	DESCRIPTION:		
DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER	55 Gallon Steel TH Drum, Any lining, with 2 in & .75 in		
CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.	Tri-Sure Fitting		

Notes: The photo shown below may or may not be identical to the description given.



