



NMFC Article	Item 294 - Semi-Liquid
NMFC Net Weight Limit	550#
UN Mark	None
Drum Type	Liquipak
Inside Diameter (A)	21-1/2"
Inside Height (B)	35"
Outside Height (C)	36"
Tare Weight (approx)	21.0#
Nominal Capacity (U.S. Gallons)	55 Gallons
Exterior Finish	Plain Kraft
Sidewall Construction (D)	Meeting or exceeding min thickness of 1100 PSI Mullen
Sidewall Adhesive	Sodium Silicate Between Each Lamination
Lining (D)	Heavy Duty Polyethylene
Barrier (D)	None
Bottom (J)	.220"/1100# PSI Heading (Thickness/Test)
Chime Band Top (F)	.025 Narrow (Stainless Steel)
Chime Band Bottom (E)	.028 Wide
Closure (G)	Galvanized Steel
Cover Type (H)	Plastic (Grey)
Cover - Gasket / Fittings / Diaphragm	Urethane / 2" & 3/4" Plugs / Removed
Additional Construction Information	None
Paint or Skin Color	None
Print Color (Silk Screen)	None
Poly Bag / Bag Option	None
Misc. Treatments	None
Special Instructions	Certificate stamp on sidewall

DISTRIBUTED BY:



REF NO.:

DWG30222

DESCRIPTION:

55 Gallon Kraft Fiber OH Drum

**DISCLAIMER**

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.