


| | | |
|---|---|--|
| | | - |
| Regulatory Information: UN 1H1/Y1.9/150 (Test Report P105) | Bill of Materials: Body: GP-55, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Fittings: 2" BTR and 2" NPS. Vented bungs are available as an option. 56X4 European BTR available. (BTR = Buttress, NPS = National Pipe Straight thread) | Product Illustration:  |

| | | | |
|---|-------------------------------------|---|---|
| Nominal Capacity: 55.0 U.S. Gallons | Outage: 2.2 U.S. Gallons | Overall Height: 34.8 inches | Nominal Total Weight: 22.2 lbs. |
| Actual Capacity: 57.2 U.S. Gallons | Outage %: 4.0 % | Body Height: 34.8 inches | Nominal Body Weight: 22.0 lbs. |
| Export Cubes: 10.41 cu. ft. | Nominal O.D.: 23.3 inches | Mid Panel Height: 10.3 inches | DOT minimum Thickness: 0.090 inches |

Special Notes:

1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.


2) Drums may be stacked 3 high (1+2) maximum with pallets between drums.
For nonvented drums, maximum top load on bottom drums not to exceed 2000 lbs each.
For vented drums, maximum top load on bottom drums not to exceed 1400 lbs each.
Pallets should be of good quality that provides adequate support for plastic drums.

3) Handle with parrotbeak, side grabber, and sling.

4) Fits four wide in standard trailer.

5) Recycle symbol embossed on bottom.

6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.

| | | |
|---|--|----------------------|
| <u>DISCLAIMER</u> THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY. | DISTRIBUTED BY:  | REF NO.: DWG30438 |
| | DESCRIPTION: 55 Gallon Natural HDPE TH Reconditioned Drum | |