



SECTION A-A

THREAD DETAIL: 6 THREADS PER INCH, 0.167" PITCH			
REFERENCE	TOLERANCE	UNITS	DIMENSION
E	±0.015 [0.38]	in [mm]	2.138 [54.30]
T	±0.015 [0.38]	in [mm]	2.235 [56.77]
H	±0.010 [0.25]	in [mm]	0.400 [10.16]
OAH	±0.012 [0.30]	in [mm]	0.459 [11.65]
OD	±0.015 [0.38]	in [mm]	2.344 [59.54]
PART WEIGHT	± 1.50	g	5.80

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG31078

DESCRIPTION: 58-400 White PP Plastic Smooth Screw  
Cap, Smooth Sides with 020 FS3-19 Liner

<b>Product</b>	.020" Pulp FS 3-19																	
<b>Scope</b>	Two piece pulp backed heat induction foil innerseal that will provide an aggressive bond with clean peel removal from PET and PVC containers. (Not recommended for use on CPET. Easy access / "puncture foil" when wax bonded to pulp.)																	
<b>Composition</b>	<table border="1"> <thead> <tr> <th>Material</th> <th>Standard</th> <th>Metric</th> </tr> </thead> <tbody> <tr> <td>Backing</td> <td>.020"</td> <td>.508 mm</td> </tr> <tr> <td>Wax</td> <td>-</td> <td>-</td> </tr> <tr> <td>Foil</td> <td>.001"</td> <td>.0254mm</td> </tr> <tr> <td>Heat Seal</td> <td>.0005"</td> <td>.0127mm</td> </tr> </tbody> </table>	Material	Standard	Metric	Backing	.020"	.508 mm	Wax	-	-	Foil	.001"	.0254mm	Heat Seal	.0005"	.0127mm		
Material	Standard	Metric																
Backing	.020"	.508 mm																
Wax	-	-																
Foil	.001"	.0254mm																
Heat Seal	.0005"	.0127mm																
Adhesive or resin bonding layers not shown.																		
<b>FDA Status:</b> 21 CFR 177.1210	<b>Recommended Storage and Handling:</b> Refer to Website																	
<b>Drug Master File (DMF):</b> #4544	<b>EU / EP Reg.:</b>																	
<b>GTR Oxygen:</b> Essentially Zero	<b>MVTR:</b> Essentially Zero																	
<b>Print Location (if any):</b> Foil Layer and/or Heat Seal Layer																		

Materials are compliant with current USFDA Food allergen Guidelines.  
Materials are compliant with California Proposition 65 labeling requirements.  
Materials are compliant with limitation of heavy metals in packaging per CONEG & EU 94/62/EC, article 11.

MSDS's are not required as Pipeline Packaging is not a chemical manufacturer or distributor and our products are 'articles' intended for food packaging per 29 CFR 1910.1200 (HazCom).

The information contained within this product data bulletin is to be used as a general guide in determining which structures are offered for sealing to specific container materials. All of the information which we provide is reliable to the best of our knowledge, but the accuracy thereof is not guaranteed. We suggest that consumers determine suitability for their own application.

DISTRIBUTED BY:	REF NO.:
	DWG31078
DESCRIPTION: 58-400 White PP Plastic Smooth Screw Cap, Smooth Sides with 020 FS3-19 Liner	

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.