

CONFORMS WITH REGULATIONS

NMFC:	Item 291
UN:	1G/Y50/S

NOMINAL DIMENSIONS

Inside Diameter:	15-1/2"
Inside Height:	14-3/4"
Outside Height:	15-3/4"
Tare Weight (approx):	6.5#
Net Packing Weight:	225#

MARKINGS

Mfg Certificate Stamp:	225#
-------------------------------	------

NOMINAL CAPACITY

U.S. Gallons:	12
----------------------	----

CONSTRUCTION – (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting minimum thickness requirements of 700 PSI Mullen.		
Sidewall Adhesive:	Polyvinyl Acetate		
Lining:	Polyester Liner		
Barrier:	N/A		
Bottom:	.120"/1000# PSI Heading (Thickness/Test)		
Chime Band Top:	Galvanized Steel	Width:	Standard
Chime Band Bottom:	Galvanized Steel	Width:	Standard
Closure:	Galvanized Steel		
Cover Type:	Plastic		
Gasket:	Urethane		
Fittings:	N/A	Diaphragm:	N/A
Additional Construction Information:	N/A		

TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	N/A		

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: