

**CONFORMS WITH REGULATIONS**

<b>NMFC:</b>	Item 291
<b>UN:</b>	1G/Y235/S

**NOMINAL DIMENSIONS**

<b>Inside Diameter:</b>	21-1/2"
<b>Inside Height:</b>	28"
<b>Outside Height:</b>	29"
<b>Tare Weight (approx):</b>	15.7#
<b>Net Packing Weight:</b>	550#

**MARKINGS**

<b>Mfg Certificate Stamp:</b>	550#
-------------------------------	------

**NOMINAL CAPACITY**

<b>U.S. Gallons:</b>	44
----------------------	----

**CONSTRUCTION – (All thickness and weights reflect minimum requirements)**

<b>Sidewall:</b>	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 1000 PSI Mullen.		
<b>Sidewall Adhesive:</b>	Sodium Silicate Between Each Lamination		
<b>Lining:</b>	N/A		
<b>Barrier:</b>	N/A		
<b>Bottom:</b>	.220"/1100# PSI Heading (Thickness/Test)		
<b>Chime Band Top:</b>	Galvanized Steel	<b>Width:</b>	Standard
<b>Chime Band Bottom:</b>	Galvanized Steel	<b>Width:</b>	Standard
<b>Closure:</b>	Galvanized Steel		
<b>Cover Type:</b>	24 Ga Steel		
<b>Gasket:</b>	N/A		
<b>Fittings:</b>	N/A	<b>Diaphragm:</b>	N/A
<b>Additional Construction Information:</b>	N/A		

**TREATMENT**

<b>Exterior Finish:</b>	Plain Kraft	<b>Paint or Skin Color:</b>	N/A
<b>Print:</b>	N/A		
<b>Print Color:</b>	N/A		
<b>Poly Bag:</b>	N/A	<b>Bag Option:</b>	N/A
<b>Misc. Treatments:</b>	N/A		

**Special Instructions:** N/A

**DISCLAIMER**

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: