

CONFORMS WITH REGULATIONS

NMFC:	Item 291
UN:	1G/Y213/S

NOMINAL DIMENSIONS

Inside Diameter:	21-1/2"
Inside Height:	34-1/2"
Outside Height:	35-1/2"
Tare Weight (approx):	17.3#
Net Packing Weight:	550#

MARKINGS

Mfg Certificate Stamp:	550#
-------------------------------	------

NOMINAL CAPACITY

U.S. Gallons:	55
----------------------	----

CONSTRUCTION – (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 1000 PSI Mullen.		
Sidewall Adhesive:	Sodium Silicate Between Each Lamination		
Lining:	N/A		
Barrier:	N/A		
Bottom:	.220"/1100# PSI Heading (Thickness/Test)		
Chime Band Top:	Galvanized Steel	Width:	Standard
Chime Band Bottom:	Galvanized Steel	Width:	Standard
Closure:	Galvanized Steel		
Cover Type:	24 Ga Steel		
Gasket:	N/A		
Fittings:	N/A	Diaphragm:	N/A
Additional Construction Information:	N/A		

TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	N/A		

Special Instructions:	N/A
------------------------------	-----

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: