

# 55 gal Open Head Kraft Fiber Drum with 2" Buttress and 3/4" NPS Fittings

## CONFORMS WITH REGULATIONS

NMFC:	Item 296 – Liquid 2A
UN:	N/A

## NOMINAL DIMENSIONS

Inside Diameter:	21-1/2"
Inside Height:	37-1/16"
Outside Height:	38-1/16"
Tare Weight (approx):	21.3#
Net Packing Weight:	700#

## MARKINGS

Mfg Certificate Stamp:	700#
------------------------	------

## NOMINAL CAPACITY

U.S. Gallons:	55
---------------	----

## CONSTRUCTION – (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 1200 PSI Mullen.		
Sidewall Adhesive:	Sodium Silicate Between Each Lamination		
Lining:	Heavy Duty Polyethylene		
Barrier:	N/A		
Bottom:	.240"/1500# PSI Heading (Thickness/Test)		
Chime Band Top:	Galvanized Steel	Width:	Wide
Chime Band Bottom:	Galvanized Steel	Width:	Wide
Closure:	Galvanized Steel		
Cover Type:	Plastic		
Gasket:	Urethane		
Fittings:	2" & 3/4" Plugs	Diaphragm:	Removed
Additional Construction Information:	N/A		

## TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	Alcohol Spray Test		

Special Instructions:	Certificate stamp on sidewall
-----------------------	-------------------------------

### DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: