

# 64 gal Open Head Kraft Fiber Drum

## CONFORMS WITH REGULATIONS

NMFC:	Item 291
UN:	N/A

## NOMINAL DIMENSIONS

Inside Diameter:	23"
Inside Height:	35-11/16"
Outside Height:	36-11/16"
Tare Weight (approx):	17.9#
Net Packing Weight:	400#

## MARKINGS

Mfg Certificate Stamp:	400#
------------------------	------

## NOMINAL CAPACITY

U.S. Gallons:	64
---------------	----

## CONSTRUCTION – (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 900 PSI Mullen.		
Sidewall Adhesive:	Sodium Silicate Between Each Lamination		
Lining:	N/A		
Barrier:	N/A		
Bottom:	.220"/1100# PSI Heading (Thickness/Test)		
Chime Band Top:	Galvanized Steel	Width:	Standard
Chime Band Bottom:	Galvanized Steel	Width:	Standard
Closure:	Galvanized Steel		
Cover Type:	Plastic		
Gasket:	Urethane		
Fittings:	N/A	Diaphragm:	N/A
Additional Construction Information:	N/A		

## TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	N/A		

Special Instructions: Certificate stamp on sidewall

## DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: