

CONFORMS WITH REGULATIONS

NMFC:	Item 296 – Liquid 2A
UN:	N/A

NOMINAL DIMENSIONS

Inside Diameter:	18-1/2"
Inside Height:	27-3/4"
Outside Height:	28-3/4"
Tare Weight (approx):	15.5#
Net Packing Weight:	600#

NOMINAL CAPACITY

U.S. Gallons: 30

CONSTRUCTION – (All thickness and weights reflect minimum requirements)

	iooo ana woigino ronoot iiiiiiii			
Sidewall:	Convolutely wound paperboard meeting or exceeding minimum			
	thickness requirements of 1200 PSI Mullen.			
Sidewall Adhesive:	Sodium Silicate Between Each Lamination			
Lining:	Heavy Duty Polyethylene			
Barrier:	N/A			
Bottom:	.240"/1500# PSI Heading (Thickness/Test)			
Chime Band Top:	Galvanized Steel with Stainless Steel Overlay Width: Standard			Standard
Chime Band Bottom:	Galvanized Steel		Width:	Wide
Closure:	Galvanized Steel			
Cover Type:	Plastic			
Gasket:	Urethane			
Fittings:	2" Bung & 3/4" Vent	Diaphragm:	iaphragm: Removed	
Additional Construction				•
Information:	N/A			

TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Colo	or: N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	Alcohol Spray Test		

Special Instructions: N/A

MARKINGS

Mfg Certificate Stamp: 600#

NOTE: All dimensions listed on the above drum are nominal. Kraft paper is subject to change with variances in relative humidity. Diameters can vary +/- 1/16". Height tolerances can vary +/- 1/4" per ft. of drum sidewall. All thicknesses and other dimensions are nominal unless otherwise stated.

DISTRIBUTED BY:

REF NO.:

DWG30845

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

ipeline Packaging

DESCRIPTION: 30 Gallon Kraft Fiber Open Head Drum, 6 mil Polyliner Lining, with Plastic Cover