



NMFC Article	Item 291 - Dry or Solid
NMFC Net Weight Limit	550#
UN Mark	1G/Y200/S/YR
Drum Type	Lok-Rim
Inside Diameter (A)	18-1/2"
Inside Height (B)	30-3/16"
Outside Height (C)	31-3/16"
Tare Weight (approx)	13.5#
Nominal Capacity (U.S. Gallons)	35 Gallons
Exterior Finish	Plain Kraft
Sidewall Construction (D)	Meeting minimum thickness of 1000 PSI Mullen
Sidewall Adhesive	Sodium Silicate Between Each Lamination
Lining (D)	None
Barrier (D)	None
Bottom (J)	.220"/1100# PSI Heading (Thickness/Test)
Chime Band Top (F)	.022 Wide
Chime Band Bottom (E)	.028 Wide
Closure (G)	Galvanized Steel
Cover Type (H)	24 Ga Steel
Cover - Gasket / Fittings / Diaphragm	None
Additional Construction Information	None

Paint or Skin Color	None
Print Color (Silk Screen)	None
Poly Bag / Bag Option	None
Misc. Treatments	None
Special Instructions	Certificate stamp on sidewall

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG30606

DESCRIPTION:

35 Gallon Fiber Lok-Rim Drum with Metal Cover