

55 gal Open Head Black Plastic Drum with 2" Buttress and 3/4" NPS Fittings

Product Specification Number: PFR55X-XX-XX-XX-XX-XX		Product Name: O-55FR	
Regulatory Information: un 1H2/Y150/S (Test Report P227) un 1H2/Y300/S - with special SLL lockband (Test Report P216)	Bill of Materials: Body: O-55FR, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Cover: Plain or Bung & Vent, HDPE. The B & V design has a 2" and a 3/4" NPS bung, with a vented 3/4" being available as an option. (NPS = National Pipe Straight thread) Lockband: Side lever (SLL)		Product Illustration: 
	Nominal Capacity: 55.0 U.S. Gallons	Outage: 2.8 U.S. Gallons	Opening I.D.: 20.3 inches
Actual Capacity: 57.8 U.S. Gallons	Outage %: 5.1 %	Nominal O.D.: 22.9 inches	Total Weight: 25.7 lbs.
Export Cubes: 9.80 cu. ft.	Overall Height: 35.2 inches	Min. Wall Thickness: 0.140 inches	Body Weight: 19.9 lbs.
Min. Blocking Diameter: 22.5 inches	Body Height: 34.9 inches	Mid Panel Height: 11.0 inches	Chime Height: 0.540 inches

Special Notes:

- Maximum filling temperature ~160°F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum.
- Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1200 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums.
- Handle with parrotbeak, side grabber, and sling.
- Recycle symbol embossed on bottom.
- Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: