Product Specification Number: PSA55X-XX-XX-XX-XX-XX		Product Name: OS-55A	
Regulatory Information:	Bill of Materials:	Product Illustration:	
un 1H2/X300/S - with 14 gauge bolt lockband (Test Report P251)	Body: OS-55A, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)	Ē	
un 1H2/Y250/S (Test Report P252)	Cover: Plain, one 2" opening, or two 2" openings available, NPS bungs, HDPE. Vented bungs are available as an option. (NPS = National Pipe Straight thread)		
	Lockband: Side lever (SLL) or Bolt		
Nominal Capacity:	Outage:	Opening I.D.:	Total Weight:
Nominal Capacity: 55.0 U.S. Gallons	Outage: 2.7 U.S. Gallons	Opening I.D.: 19.3 inches	Total Weight: 24.3 lbs.
55.0 U.S. Gallons	2.7 U.S. Gallons	19.3 inches	24.3 lbs.
55.0 U.S. Gallons Actual Capacity:	2.7 U.S. Gallons Outage %:	19.3 inches Nominal O.D.:	24.3 lbs. Body Weight:
55.0 U.S. Gallons Actual Capacity: 57.7 U.S. Gallons	2.7 U.S. Gallons Outage %: 5.0 %	19.3 inches Nominal O.D.: 23.2 inches	24.3 lbs. Body Weight: 19.6 lbs. Chime Height:
55.0 U.S. Gallons Actual Capacity: 57.7 U.S. Gallons Export Cubes:	2.7 U.S. Gallons Outage %: 5.0 % Overall Height:	19.3 inches Nominal O.D.: 23.2 inches Min. Wall Thickness:	24.3 lbs. Body Weight: 19.6 lbs.

55 gal Open Head Blue Plastic Drum with 2" Buttress and 2" NPT Fittings

Special Notes:

- Maximum filling temperature 150 F. When filled 5) at this recommended maximum filling temperature drums should be allowed to cool to 6) ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.
- Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 600 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums.
- 3) Handle with parrotbeak, side grabber, and sling.
- 4) Recycle symbol embossed on bottom.

Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.

- Manufactured at the following locations:
- Houston, with heavyweight cover
- ² Houston, with lightweight cover
- ³ Houston, Hazleton and Lockport with lightweight cover
- Lockport weight is body / assembled 10.7/14.0 lbs nominal
- Hazleton weight is body / assembled 10.4/13.7 lbs nominal
- Available only from Lockport with total drum weight 15.3 lbs.

DISCLAIMER	DISTRIBUTED BY		REF NO.:
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT		ipeline Packaging	
THE PROPER CONTAINER FOR PRODUCT AND APPLICATION	DESCRIPTION:		
COMPATIBILITY.			