



30 gal Open Head Blue Plastic Drum

Product Specification Number: PSL30X-XX-XX-XX-XX-XX		Product Name: OS-30L	
Regulatory Information: UN 1H2/Y180/S (Test Report P247)	Bill of Materials: Body: OS-30L, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Cover: Plain or Bung & Vent, HDPE. The B & V design has a 2" and a 3/4" NPS bung, with a vented 3/4" being available as an option. (NPS = National Pipe Straight thread) Lockband: Side lever (SLL) or Bolt	Product Illustration: 	
Nominal Capacity: 30.0 U.S. Gallons	Outage: 2.1 U.S. Gallons	Opening I.D.: 17.5 inches	Total Weight: 14.4 lbs.
Actual Capacity: 32.1 U.S. Gallons	Outage %: 7.0 %	Nominal O.D.: 19.6 inches	Body Weight: 10.7 lbs.
Export Cubes: 5.85 cu. ft.	Overall Height: 28.2 inches	Min. Wall Thickness: 0.125 inches	Chime Height: 0.530 inches
Min. Blocking Diameter: 19.4 inches	Body Height: 27.9 inches	Mid Panel Height: 9.1 inches	

Special Notes:

- 1) Maximum filling temperature ~160°F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum.
- 3) Handle with parrotbeak, side grabber, and sling.
- 4) Recycle symbol embossed on bottom.
- 5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.
- 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 600 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums.

DISCLAIMER	DISTRIBUTED BY: 	REF NO.:
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.	DESCRIPTION:	