



<b>Product Specification Number:</b> PSO30X-XX-XX-XX-XX		<b>Product Name:</b> <b>OS-30</b>	
<b>Regulatory Information:</b>  un 1H2/X150/S <sup>1</sup> (Test Report P245)  un 1H2/X125/S <sup>2</sup> (Test Report P244)  un 1H2/Y180/S <sup>3</sup> (Test Report P246)  UN 1H2/Y260/S (Test report P402, note 9)  UN 1H2/Y100/S (Test report P236)	<b>Bill of Materials:</b>  <b>Body:</b> OS-30, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)  <b>Cover:</b> Plain or Bung & Vent, HDPE. The B & V design has a 2" and a 3/4" NPS bung, with a vented 3/4" being available as an option. (NPS = National Pipe Straight thread)  <b>Lockband:</b> Side lever (SLL), Bolt and plastic.	<b>Product Illustration:</b> 	
<b>Nominal Capacity:</b> 30.0 U.S. Gallons	<b>Outage:</b> 2.2 U.S. Gallons	<b>Opening I.D.:</b> 17.5 inches	<b>Total Weight:</b> 14.6 lbs.
<b>Actual Capacity:</b> 32.2 U.S. Gallons	<b>Outage %:</b> 7.3 %	<b>Nominal O.D.:</b> 19.3 inches	<b>Body Weight:</b> 11.3 lbs.
<b>Export Cubes:</b> 6.05 cu. ft.	<b>Overall Height:</b> 29.4 inches	<b>Min. Wall Thickness:</b> 0.125 inches	<b>Chime Height:</b> 0.530 inches
<b>Min. Blocking Diameter:</b> 18.7 inches	<b>Body Height:</b> 29.1 inches	<b>Mid Panel Height:</b> 11.4 inches	
<b>Special Notes:</b> 1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability. 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 600 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Recycle symbol embossed on bottom. 5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 6) Manufactured at the following locations: <sup>1</sup> Houston, with heavyweight cover <sup>2</sup> Houston, with lightweight cover <sup>3</sup> Houston, Hazleton and Lockport with lightweight cover 7) Lockport weight is body / assembled 10.7/14.0 lbs nominal 8) Hazleton weight is body / assembled 10.4/13.7 lbs nominal 9) Available only from Lockport with total drum weight 15.3 lbs.			

### 30 gal Open Head Blue Plastic Drum with 3/4" EPDM

<b>DISCLAIMER</b>  THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.	DISTRIBUTED BY:  ipeline Packaging	REF NO.:
	DESCRIPTION:	