

# 55 gal Open Head Blue Plastic Drum

<b>Product Specification Number:</b> PSA55X-XX-XX-XX-XX-XX		<b>Product Name:</b> <b>OS-55A</b>	
<b>Regulatory Information:</b>  un 1H2/X300/S - with 14 gauge bolt lockband (Test Report P251)  un 1H2/Y250/S (Test Report P252)	<b>Bill of Materials:</b>  <b>Body:</b> OS-55A, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)  <b>Cover:</b> Plain, one 2" opening, or two 2" openings available, NPS bungs, HDPE. Vented bungs are available as an option. (NPS = National Pipe Straight thread)  <b>Lockband:</b> Side lever (SLL) or Bolt	<b>Product Illustration:</b> 	
	<b>Nominal Capacity:</b> 55.0 U.S. Gallons	<b>Outage:</b> 2.7 U.S. Gallons	<b>Opening I.D.:</b> 19.3 inches
<b>Actual Capacity:</b> 57.7 U.S. Gallons	<b>Outage %:</b> 5.0 %	<b>Nominal O.D.:</b> 23.2 inches	<b>Total Weight:</b> 23.1 lbs.
<b>Export Cubes:</b> 11.02 cu. ft.	<b>Overall Height:</b> 36.8 inches	<b>Min. Wall Thickness:</b> 0.135 inches	<b>Body Weight:</b> 19.3 lbs.
<b>Min. Blocking Diameter:</b> 22.2 inches	<b>Body Height:</b> 36.5 inches	<b>Chime Height:</b> 0.480 inches	<b>Mid Panel Height:</b> 11.5 inches
<b>Special Notes:</b> 1) Maximum filling temperature 150 F for all foods and other FDA regulated substances. 160 F for all non-foods and other substances that are not regulated by FDA. When filled at these recommended maximum filling temperatures drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability. 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1300 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Recycle symbol embossed on bottom. 5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.			

## DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: