



Product Specification Number: PMB48X-XX-XX-XX-XX-XX		Product Name: O-48MB			
Regulatory Information: un 1H2/X100/S (Test Report P219) un 1H2/Y150/S (Test Report P220) un 1H2/Y165/S (note 8) (Test Report P422) un 1H2/Z260/S (note 8) (Test Report P424)		Bill of Materials: Body: O-48MB, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Cover: Plain, one 2" opening, or two 2" openings available, NPS bungs, HDPE. Vented bungs are available as an option. (NPS = National Pipe Straight thread) Lockband: Side lever (SLL) or Bolt			
Product Illustration:					
Nominal Capacity: 48.0 U.S. Gallons	Outage: 2.5 U.S. Gallons			Opening I.D.: 22.0 inches	Total Weight: 20.2 lbs.
Maximum Capacity: 50.5 U.S. Gallons	Outage %: 5.2 %			Nominal O.D.: 23.8 inches	Body Weight: 15.5 lbs.
Export Cubes: 10.41 cu. ft.	Overall Height: 34.1 inches			Taper Height: 21.5 inches	Nesting Height: 11.1 inches
Min. Blocking Diameter: 20.4 inches	Body Height: 33.8 inches			Min. Wall Thickness: 0.090 inches	Chime Height: 0.530 inches
Special Notes:					
1) Maximum filling temperature 150 F for all foods and other FDA regulated substances. 160 F for all non-foods and other substances that are not regulated by FDA. When filled at these recommended maximum filling temperatures drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1000 lbs. each. Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Drums are fully nestable without airlocking. 5) Recycle symbol embossed on bottom. 6) Patent number 5,881,898 embossed on drum. 7) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 8) These reports for Mt. Sterling only.					

temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.

2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1000 lbs. each. Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:  REF NO.:

DESCRIPTION: