


# 14 gal Open Head Nestable Black Plastic Drum

<b>Product Specification Number:</b> POX14X-XX-XX-XX-XX-XX		<b>Product Name:</b> <b>O-14</b>	
<b>Regulatory Information:</b>  un 1H2/X65/S <sup>1</sup> (Test Report P205LK) (Test Report P203HS)  un 1H2/Y100/S <sup>2</sup> (Test Report P204LK) (Test Report P304HS)	<b>Bill of Materials:</b>  <b>Body:</b> O-14, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)  <b>Cover:</b> Plain or Bung & Vent, HDPE. The B & V design has a 2" and a 3/4" NPS bung, with a vented 3/4" being available as an option. (NPS = National Pipe Straight thread)  <b>Lockband:</b> Side lever (SLL) or Bolt	<b>Product Illustration:</b> 	
	<b>Nominal Capacity:</b> 14.0 U.S. Gallons	<b>Outage:</b> 0.9 U.S. Gallons	<b>Opening I.D.:</b> 13.7 inches
<b>Maximum Capacity:</b> 14.9 U.S. Gallons	<b>Outage %:</b> 6.4 %	<b>Nominal O.D.:</b> 14.9 inches	<b>Body Weight:</b> 6.5 lbs.
<b>Export Cubes:</b> 2.95 cu. ft.	<b>Overall Height:</b> 26.3 inches	<b>Taper Height:</b> 15.8 inches	<b>Nesting Height:</b> 9.4 inches
<b>Min. Blocking Diameter:</b> 13.0 inches	<b>Body Height:</b> 25.9 inches	<b>Min. Wall Thickness:</b> 0.090 inches	<b>Chime Height:</b> 0.525 inches
<b>Special Notes:</b>			
<p>1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.</p> <p>2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 750 lbs. each. May be stacked two (2) drums high per pallet with slip sheet of plywood between layers of drums with top load not exceeding the specified limit.</p> <p>2) Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums.</p> <p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Drums are fully nestable without airlocking.</p> <p>5) Recycle symbol embossed on bottom.</p> <p>6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.</p> <p>7) Manufactured at the following locations:          * Houston and Lockport          * Lockport</p>			

### DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: