



20 gal Open Head Nestable Natural Plastic Drum

Product Specification Number: PMB20X-XX-XX-XX-XX-XX		Product Name: O-20MB	
Regulatory Information: un 1H2/Y130/S (Test Report P212) un 1H2/Y130/S (Test Report P283)	Bill of Materials: Body: O-20MB, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Cover: Plain or Bung & Vent, HDPE. The B & V design has a 2" and a 3/4" NPS bung, with a vented 3/4" being available as an option. (NPS = National Pipe Straight thread) Lockband: Side lever (SLL) or Bolt	Product Illustration: 	
Nominal Capacity: 20.0 U.S. Gallons	Outage: 0.2 U.S. Gallons	Opening I.D.: 15.6 inches	Total Weight: 10.0 lbs.
Actual Capacity: 20.2 U.S. Gallons	Outage %: 1.0 %	Nominal O.D.: 15.9 inches	Body Weight: 7.5 lbs.
Export Cubes: 3.91 cu. ft.	Overall Height: 30.5 inches	Taper Height: 19.3 inches	Nesting Height: 8.9 inches
Min. Blocking Diameter: 13.5 inches	Body Height: 30.1 inches	Min. Wall Thickness: 0.090 inches	Chime Height: 0.505 inches

Special Notes:

- 1) Maximum filling temperature 150 degrees F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.
- 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 750 lbs. each. Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums.
- 3) Handle with parrotbeak, side grabber, and sling.
- 4) Drums are fully nestable without airlocking.
- 5) Recycle symbol embossed on bottom.
- 6) Patent number 5,881,898 embossed on drum.
- 7) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.

DISCLAIMER	DISTRIBUTED BY: 	REF NO.:
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.		DESCRIPTION: