



## 40 gal Open Head Nestable Blue Plastic Drum

<b>Product Specification Number:</b> PMB40X-XX-XX-XX-XX-XX		<b>Product Name:</b> <b>O-40MB</b>	
<b>Regulatory Information:</b>  un 1H2/X100/S (Test Report P219)  un 1H2/Y150/S (Test Report P220)  un 1H2/Z175/S (Test Report P221)	<b>Bill of Materials:</b>  <b>Body:</b> O-40MB, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)  <b>Cover:</b> Plain or with 2 x 2" NPS or Bung & Vent, HDPE. The B & V design has a 2" and a ¼" NPS bung, with a vented ¼" being available as an option. (NPS = National Pipe Straight thread)  <b>Lockband:</b> Side lever (SLL) or Bolt	<b>Product Illustration:</b> 	
<b>Nominal Capacity:</b> 40.0 U.S. Gallons	<b>Outage:</b> 2.4 U.S. Gallons	<b>Opening I.D.:</b> 22.0 inches	<b>Total Weight:</b> 19.2 lbs.
<b>Actual Capacity:</b> 42.4 U.S. Gallons	<b>Outage %:</b> 6.0 %	<b>Nominal O.D.:</b> 23.8 inches	<b>Body Weight:</b> 14.2 lbs.
<b>Export Cubes:</b> 9.18 cu. ft.	<b>Overall Height:</b> 30.1 inches	<b>Taper Height:</b> 21.5 inches	<b>Nesting Height:</b> 7.1 inches
<b>Min. Blocking Diameter:</b> 20.4 inches	<b>Body Height:</b> 29.8 inches	<b>Min. Wall Thickness:</b> 0.130 inches	<b>Chime Height:</b> 0.530 inches

**Special Notes:**

- |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>1) Maximum filling temperature ~160°F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum.</p> <p>2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1000 lbs. each. Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums.</p> | <p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Drums are fully nestable without airtlocking.</p> <p>5) Recycle symbol embossed on bottom.</p> <p>6) Patent number 5,881,898 embossed on drum.</p> <p>7) Compatibility with hazardous materials as listed 49CFR are the responsibility of the filler.</p> <p>8) Produced in Mt. Sterling at a drum body weight  13.3 lbs. (total weight of 18.3 lbs.)</p> |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

<b>DISCLAIMER</b>	DISTRIBUTED BY:  Pipeline Packaging	REF NO.:
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.	DESCRIPTION:	