



55 gal Open Head Nestable Black Plastic Drum

Product Specification Number: PBT55X-XX-XX-XX-XX-XX		Product Name: O-55BT			
Regulatory Information: un 1H2/Y185/S ¹ (test report P237) un 1H2/Y170/S ² (Test Report P226) un 1H2/Y100/S (Test Report P405, special note 8)		Bill of Materials: Body: O-55BT, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Cover: Plain, one 2" opening, or two 2" openings available, NPS bungs, HDPE. Vented bungs are available as an option. (NPS = National Pipe Straight thread) Lockband: Side lever (SLL) or Bolt or plastic lockband			
Product Illustration:					
Nominal Capacity: 55.0 U.S. Gallons	Outage: 0.9 U.S. Gallons			Opening I.D.: 22.0 inches	Total Weight: 22.5 lbs.
Maximum Capacity: 55.9 U.S. Gallons	Outage %: 1.6 %			Nominal O.D.: 23.8 inches	Body Weight: 17.5 lbs.
Export Cubes: 11.63 cu. ft.	Overall Height: 38.8 inches			Taper Height: 31.0 inches	Nesting Height: 6.7 inches
Min. Blocking Diameter: 19.7 inches	Body Height: 38.5 inches			Min. Wall Thickness: 0.090 inches	Chime Height: 0.530 inches
Special Notes:					
<p>1) Maximum filling temperature 150 degrees F. When filled at these recommended maximum filling temperatures drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.</p> <p>2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 600 lbs. each. Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums.</p> <p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Drums are fully nestable without airlocking.</p> <p>5) Recycle symbol embossed on bottom.</p> <p>6) Patent number 5,881,898 embossed on drum.</p> <p>7) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.</p> <p>8) Available from LaPalma with plastic lockband at Y100. Total weight 20.9 lbs.</p> <p>9) Manufactured at the following locations: ¹ Lockport & LaPalma ² Houston</p>					

DISCLAIMER	DISTRIBUTED BY: 	REF NO.:
	DESCRIPTION:	

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.