

15 gal Tight Head Blue Plastic Drum with 2" Buttress and 3/4" NPS Fittings

Product Specification Number: PPK15X-XX-XX-XX-XX-XX		Product Name: PIK-15	
Regulatory Information: un 1H1/Y1.9/150 (Test Report P170) un 1H1/Y1.4/150 with vent (Test Report P171) un 1H1/Y1.8/150 (Test Report P168)	Bill of Materials: Body: PIK-15, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Fittings: 2" and 3/4" NPS and 2" Buttress (see note 6) Vented bungs are available as an option. (NPS = National Pipe Straight thread)	Product Illustration: 	
Nominal Capacity: 15.0 U.S. Gallons	Outage: 1.5 U.S. Gallons	Overall Height: 26.1 inches	Total Weight: 7.0 lbs.
Actual Capacity: 16.5 U.S. Gallons	Outage %: 10.0 %	Body Height: 26.1 inches	Body Weight: 6.8 lbs.
Export Cubes: 2.95 cu. ft.	Nominal O.D.: 14.4 inches	Mid Panel Height: 15.6 inches	Min. Wall Thickness: 0.090 inches

Special Notes:

- 1) Maximum filling temperature 150 F for all foods and other FDA regulated substances. 160 F for all non-foods and other substances that are not regulated by FDA. When filled at these recommended maximum filling temperatures drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.
- 2) Drums may be stacked 4 high (1+3) maximum with pallets between drums.
For nonvented drums, maximum top load on bottom drums not to exceed 1000 lbs each.
For vented drums, maximum top load on bottom drums not to exceed 500 lbs each.
Pallets should be of good quality that provides adequate support for plastic drums.
- 3) Volume markers available.
- 4) Recycle symbol embossed on bottom.
- 5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.
- 6) Available configured with only 2" Buttress fitting from Hazleton.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: