

20 gal Tight Head Blue Plastic Drum with 2" Buttress and 2" NPT Fittings

Product Specification Number: PPA20X-XX-XX-XX-XX-XX		Product Name: P-20A	
Regulatory Information: un 1H1/Y2.0/150 (Test Report P111) un 1H1/Y1.4/150 (Test Report P118) ** (see special note 6)	Bill of Materials: Body: P-20A, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Fittings: 2" BTR and 2" NPS. Available configured with a single BTR. (BTR = Buttress, NPS = National Pipe Straight thread)	Product Illustration: 	
	Nominal Capacity: 20.0 U.S. Gallons	Outage: 1.4 U.S. Gallons	Overall Height: 27.1 inches
Maximum Capacity: 21.4 U.S. Gallons	Outage %: 6.9 %	Body Height: 27.1 inches	Body Weight: 9.8 lbs.
Export Cubes: 4.00 cu. ft.	Nominal O.D.: 16.0 inches	Mid Panel Height: 22.6 inches	Min. Wall Thickness: 0.110 inches
Special Notes:			
1) Maximum filling temperature 150 F for all foods and other FDA regulated substances. 160 F for all non-foods and other substances that are not regulated by FDA. When filled at these recommended maximum filling temperatures drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures		3) Volume markers available. 4) Recycle symbol embossed on bottom. 5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 6) Test report P118: rating with single 2" Buttress Fitting.	

should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.

2) Stack 4 high (1+3) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1200 lbs each. Pallets should be of good quality that provides adequate support for plastic drums.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: