


55 gal Tight Head Blue Plastic Drum with 2" Buttress and 2" NPS EPDM Gasket Fittings

Product Specification Number: PGP55X-XX-XX-XX-XX-XX		Product Name: GP-55	
Regulatory Information: un 1H1/Y1.9/150 (Test Report P108) un 1H1/Y1.4/150 with vent (Test Report P102)	Bill of Materials: Body: GP-55, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Fittings: 2" BTR and 2" NPS. Vented bungs are available as an option. (BTR = Buttress, NPS = National Pipe Straight thread)	Product Illustration: 	
Nominal Capacity: 55.0 U.S. Gallons	Outage: 2.2 U.S. Gallons	Overall Height: 34.8 inches	Total Weight: 21.0 lbs.
Actual Capacity: 57.2 U.S. Gallons	Outage %: 4.0 %	Body Height: 34.8 inches	Body Weight: 20.8 lbs.
Export Cubes: 10.41 cu. ft.	Nominal O.D.: 23.3 inches	Mid Panel Height: 10.3 inches	Min. Wall Thickness: 0.140 inches

Special Notes:

- | | |
|--|---|
| <p>1) Maximum filling temperature ~160°F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum.</p> <p>2) Drums may be stacked 3 high (1+2) maximum with pallets between drums.
For nonvented drums, maximum top load on bottom drums not to exceed 2000 lbs each.
For vented drums, maximum top load on bottom drums not to exceed 1400 lbs each.
Pallets should be of good quality that provides adequate support for plastic drums.</p> | <p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Fits four wide in standard trailer.</p> <p>5) Recycle symbol embossed on bottom.</p> <p>6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.</p> |
|--|---|

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: